



BH-620



BH-800

Optional device

- Nitrogen gas flushing
- Gusset device
- Air expeller
- Hole punch device
- Tear notch device
- Material stopper
- Safety device
- Bag support
- PE sealing system
- Vacuum device
- Flip device
- Static eliminator
- 4 lines folding device
- Film tracking device
- Special sealing jaws

Bag style



Packing material

Heat sealable roll film

- Single-layer PE
- Laminated film
- Various complex films

Model	BH-500	BM-500	BH-620	BM-620	BH-800	BM-800
Frame structure	Stainless steel	Mild steel painted	Stainless steel	Mild steel painted	Stainless steel	Mild steel painted
Film width	180-500mm		240-620mm		340-800mm	
Bag length	60-300mm		70-380mm		100-480mm	
Speed	Max. 70 bpm		Max. 60 bpm		Max. 45 bpm	
Power supply	220V, 50/60HZ, 3 KW		220V, 50/60HZ, 4 KW		220V, 50/60HZ, 4.5 KW	
Air requests	0.36m ³ /min, 0.6Mpa		0.4m ³ /min, 0.6Mpa		0.6m ³ /min, 0.6Mpa	
Outer dimension	1420x1160x1480mm		1480x1260x1680mm		1600x1500x2050mm	