

## Data sheet: Fillogy Flowable L (Art. 301053)

### Description

Machine for the dosed filling of non-flowable and viscous products, e.g:

- fruit puree, spreads, chutney (up to 3mm piece size)
- mustard, ketchup
- creamy yoghurt
- dyestuffs and flavours for the food industry
- lotion, ointments and hair colours
- water soluble lacquers, artist colours (oil/acrylic/gouache), wood glue



Main field of application: filling of container sizes from 50 to 500 g

### Customer benefit

Precise and effective dosing of products that are manually difficult to dose.

### Operating conditions

Hours of operation per day: 8  
 Days of operation per week: 5  
 Ambient temperature: 10 - 40°C

### Technical Data

Nominal voltage: 24 V DC (power supply for 220 V enclosed)  
 Power consumption: 30 - 240 W  
 Motor speed: 50 - 250 rpm  
 Footprint: width 350 mm x depth 350 mm  
 Total height: 700 mm (optional 1,000 mm)  
 Height under filling nozzle: 10 – 235 mm  
 Weight: 16.4 kg (without power supply)  
 Dosage with step size
 

- 0.1 g: 0.1 - 49.9 g
- 1.0 g: 50.0 – 32,500.0 g

 Filling accuracy: Maximal 2% deviation  
 Maximum suction lift: n. a.  
 Maximum volume flow: 14.0 l/min  
 Filling temperature: 2 - 95°C

### Triggering of the filling process

Foot switch (included)  
 Frame switch (included)  
 Sensor (optional for operation with rotary table)

### Automatability

In part